



ME by Starck Handrinse basin # 071945..00 / 071945..00 /
071945..10 / 071945..10

| < 450 mm > |



Handrinse basin	Dimension	Weight	Order number
with overflow, with tap platform, underneath glazed, 450 mm			
Colors			
00 White Alpin 32 White Satin Matt			
Variant			
●	450 x 320 mm	9.800 kilogram	071945..00
●	450 x 320 mm	9.800 kilogram	071945..00
●	450 x 320 mm	9.800 kilogram	071945..10
●	450 x 320 mm	9.800 kilogram	071945..10
Sanitary ceramics with the special WonderGliss surface finish will remain clean and attractive-looking for a long time to come. When ordering WonderGliss please add a "1" as eleventh digit to the model number.			
Suitable products			
Siphon cover for # 071945, 165 x 230 mm	165 x 230 mm		085841
Recommended faucets			
Single lever basin mixer S ceramic cartridge, Projection 101 mm, flexible connection hoses 3/8", aerator adjustable, normal spray, chrome, maximum temperature can be adjusted on installation, recommended operating pressure 1 - 5 bar, with pop-up waste set,			B21010001
Single lever basin mixer S ceramic cartridge, Projection 101 mm, flexible connection hoses 3/8", aerator adjustable, normal spray, chrome, maximum temperature can be adjusted on installation, recommended operating pressure 1 - 5 bar, without pop-up waste set,			B11010002
Single lever basin mixer S ceramic cartridge, Projection 101 mm, flexible connection hoses 3/8", aerator adjustable, normal spray, chrome, maximum temperature can be adjusted on installation, recommended operating pressure 1 - 5 bar, with pop-up waste set,			B11010001

ME by Starck Handrinse basin # 071945..00 / 071945..00 / 071945..10 / 071945..10

| < 450 mm > |

Single lever basin mixer S ceramic cartridge, Projection 101 mm, flexible connection hoses 3/8", aerator adjustable, normal spray, chrome, maximum temperature can be adjusted on installation, recommended operating pressure 1 - 5 bar, without pop-up waste set,	B21010002
Single lever basin mixer S ceramic cartridge, Projection 94 mm, flexible connection hoses 3/8", aerator adjustable, normal spray, chrome, maximum temperature can be adjusted on installation, recommended operating pressure 1 - 5 bar, with pop-up waste set,	DE1010001
Single lever basin mixer S ceramic cartridge, Projection 94 mm, flexible connection hoses 3/8", aerator adjustable, normal spray, chrome, maximum temperature can be adjusted on installation, recommended operating pressure 1 - 5 bar, without pop-up waste set,	DE1010002
Single lever basin mixer S FreshStart ceramic cartridge, in centre position cold water, Projection 94 mm, flexible connection hoses 3/8", aerator adjustable, normal spray, chrome, maximum temperature can be adjusted on installation, recommended operating pressure 1 - 5 bar, with pop-up waste set,	DE1011001
Single lever basin mixer S FreshStart ceramic cartridge, in centre position cold water, Projection 94 mm, flexible connection hoses 3/8", aerator adjustable, normal spray, chrome, maximum temperature can be adjusted on installation, recommended operating pressure 1 - 5 bar, without pop-up waste set,	DE1011002
Single lever basin mixer S FreshStart ceramic cartridge, in centre position cold water, projection 110 mm, flexible connection hoses 3/8", flow rate 5,0 l/min (3 bar), normal spray, connection size DN15, maximum temperature can be adjusted on installation, recommended operating pressure 1 - 5 bar, with pop-up waste set,	TU1011001
Single lever basin mixer S FreshStart ceramic cartridge, in centre position cold water, projection 110 mm, flexible connection hoses 3/8", flow rate 5,0 l/min (3 bar), normal spray, connection size DN15, maximum temperature can be adjusted on installation, recommended operating pressure 1 - 5 bar, without pop-up waste set,	TU1011002
Single lever basin mixer S ceramic cartridge, projection 110 mm, flexible connection hoses 3/8", flow rate 5,0 l/min (3 bar), normal spray, connection size DN15, maximum temperature can be adjusted on installation, recommended operating pressure 1 - 5 bar, with pop-up waste set,	TU1010001
Single lever basin mixer S ceramic cartridge, projection 110 mm, flexible connection hoses 3/8", flow rate 5,0 l/min (3 bar), normal spray, connection size DN15, maximum temperature can be adjusted on installation, recommended operating pressure 1 - 5 bar, without pop-up waste set,	TU1010002

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in mm and are non-binding. Exact measurements, in particular for customised installation scenarios, can only be taken from the finished piece.